

# ST STEEL HIGH SIDE

	SA 5' x 8'	SA 5' x 10'	SA 6' x 10'	SA 6' x 12'	SA 7' x 12'	TA 7' x 16'
<b>Model #</b>	ST6208HSA-B-030	ST6210HSA-B-030	ST7210HSA-B-030	ST7212HSA-B-030	ST8212HSA-B-030	ST8216HSAT-B-070
<b>GVWR (lb.)</b>	2990	2990	2990	2990	2990	7000
<b>GAWR (lb. / axle)</b>	3500	3500	3500	3500	3500	3500
<b>Curb Weight</b>	990	1060	1110	1230	1380	1950
<b>Payload</b>	2000	1930	1880	1760	1610	5050
<b>Cross Members</b>	3 x 2 x 3/16 Angle (24" On-Center)					
<b>Tongue</b>	3" Channel (A-Frame)			4" Channel (A-Frame)		
<b>Frame/Sides</b>	14 ga. 13" Fabricated Solid Steel					
<b>Coupler</b>	2" A-Frame Coupler					2-5/16" A-Frame Coupler
<b>Jack</b>	Setback 2K Zinc Plated Jack					
<b>Fenders</b>	Tread Plate, Square Rolled					Tread Plate, Double Brake
<b>Easy Lube Axles</b>	Cambered Idler with brake flange					Cambered Brake (Both Axles)
<b>Suspension</b>	Leaf Spring					Equalized Leaf Spring
<b>Tires</b>	205/75R15 LRC					
<b>Wheels</b>	15", 5 on 4.5, Radial Tire					
<b>Decking</b>	2 x 6 Pressure Treated Pine					
<b>Lights</b>	All LED Lights					
<b>Electric Plug</b>	4-Way Flat Molded Plug					7-Way RV-Style Molded Plug
<b>Finish</b>	Powder Coated High Gloss Black					
<b>Overall Length</b>	137"	161"	161"	185"	185"	237"
<b>Bed Length</b>	96"	120"	120"	144"	144"	192"
<b>Bed Width</b>	61.5"	61.5"	71.5"	71.5"	81.5"	81.5"
<b>Deck Height</b>	18"	18"	18"	18"	18"	18"
<b>Coupler Height</b>	16"	16"	16"	16"	16"	16"
<b>Gate</b>	2 x 2 Tube, Mesh Covered, Full-Width Spring-Assist Ramp Gate with Handle					

## STEEL HIGH SIDE STANDARD FEATURES

13" Solid Steel Sides	Setback 2K Zinc Plated Jack	Silver Wheels
4" Tie-Down Rail	Fold-Flat HD Ramp Gate with Handle	Wheel Assembly, 205 75R15 LRC
2" A-Frame Coupler (SA Models)	Spring-Assisted Rear Ramp Gate	Powder Coat Finish
2-5/16" A-Frame Coupler (TA Models)	Self-Retained Gate Pins	Pressure Treated 2" x 6" Decking
Safety Chains	Tread Plate Fenders	Front and Rear Board Retainers
4-Way Flat Molded Plug (SA Models)	Idler Axle (SA Models)	(4) 1/2" D-rings (SA Models)
7-Way RV-Style Molded Plug (TA Models)	Brakes on Both Axles (TA Models)	(6) 1/2" D-rings (TA Models)
Breakaway Switch with Battery (TA Models)	Easy Lube Hubs	Spare Tire Carrier
Wiring Enclosed in Tubular Steel	15" Radial Tires	All LED Lights

